



**E25**

GAS FIREPLACE INSERT



[enviro.com](http://enviro.com)

# E25

## GAS FIREPLACE INSERT




### Insert Specifications

BTU Maximum Input - NG	28,000 BTU
BTU Minimum Output*	14,000 BTU
Heating Area	1,600 ft <sup>2</sup>
P4 Efficiency	TBA
Glass Size	420 in <sup>2</sup>
Minimum Install Dims.	HEIGHT: 19 <sup>7</sup> / <sub>8</sub> "    WIDTH: 27 <sup>7</sup> / <sub>8</sub> "    DEPTH: 13 <sup>3</sup> / <sub>4</sub> "

\* Turn down is based on a 50% valve.

### Clearance to Combustibles

Mantle pillar to the edge the of glass	21"
Min. non-combustible surface in front of unit	16"
Floor to an 8" wide mantle	36"



### Design Features

- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 26<sup>1</sup>/<sub>4</sub>" x 16", 420 in<sup>2</sup>
- Included Traditional Log Set
- Easy Access Burner Switch (NOVA)
- Stainless Steel Burner
- Steel Firebox Grate
- Enviro's Smallest Install Depth - Only 13<sup>3</sup>/<sub>4</sub>"
- Limited Lifetime Warranty

### Gas Insert Options

- Hearth Riser
- Traditional Log Set - Included
- Liner Options:
  - Painted Liner - Included
  - Brick Liner
- Surround Options:
  - Surround Panel - Included 25<sup>3</sup>/<sub>4</sub>" x 39"
  - Trimmable Panel 30.2" x 48"
- Optional 110 CFM Fan - Included with IPI



Manufactured by Sherwood Industries Ltd • Victoria, BC, Canada  
enviro.com • info@enviro.com • Printed in Canada, May 2020

Designed & Built in  
**North America**