



E25

GAS FIREPLACE INSERT



enviro.com

E25

GAS FIREPLACE INSERT




Insert Specifications

BTU Maximum Input - NG	28,000 BTU
BTU Minimum Output*	14,000 BTU
Heating Area	1,600 ft ²
P4 Efficiency	63.9%
Glass Size	26¼" x 16"
Minimum Install Dims.	HEIGHT: 19 ⁷ / ₈ " WIDTH: 27 ⁷ / ₈ " DEPTH: 13 ¹ / ₂ "

* Turn down is based on a 50% valve.

Clearance to Combustibles

A	Mantle pillar to the edge the of glass	21"
B	Min. non-combustible surface in front of unit	16"
C	Floor to an 8" wide mantle	36"



Design Features

- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 26¼" x 16", 420 in²
- Included Traditional Log Set
- Easy Access Burner Switch (NOVA)
- Stainless Steel Burner
- Steel Log Grate
- Enviro's Smallest Install Depth - Only 13½"
- Limited Lifetime Warranty

Gas Insert Options

- Hearth Riser
- Traditional Log Set - Included
- Liner Options:
 - Painted Liner - Included
 - Brick Liner
- Surround Options:
 - Surround Panel - Included 25¾" x 39"
 - Trimmable Panel 30.2" x 48"
- Optional 110 CFM Fan - Included with IPI



Manufactured by Sherwood Industries Ltd • Victoria, BC, Canada
enviro.com • info@enviro.com • Printed in Canada, June 2021

Designed & Built in
North America